

NANOPROOF

SOLAR FILMS

NANOPROOF TECHNICAL SPECIFICATIONS

ZR PRO SERIES

Product Code	Thickness	Visible Light Transmittance (VLT)	UV Rejection	BTU Rejection (400nm to 950nm)	IRR Rejection (940nm to 1400nm)	IRR Rejection (760nm to 1750nm)	TSER	Shade Level
ZR PRO - 05	2 MIL	4.5%	99.0%	98.0%	98.1%	98.0%	78.0%	70.0%
ZR PRO - 10	2 MIL	10.0%	99.5%	97.0%	97.5%	97.0%	74.0%	50.0%
ZR PRO - 20	2 MIL	20.0%	98.9%	97.0%	98.0%	97.0%	70.0%	30.0%
ZR PRO - 40	2 MIL	40.0%	98.5%	95.0%	97.5%	94.0%	61.0%	10.0%
ZR PRO - 60	2 MIL	59.0%	98.8%	93.0%	96.7%	93.0%	59.0%	5.0%
ZR PRO - 70	2 MIL	64.0%	99.0%	95.0%	98.4%	95.0%	56.0%	0/0

WARRANTY

Durability

10 Years

- ZR PRO series comes with a 10 year warranty against delamination, peeling, blistering, failure of adhesion, and other manufacturing defects.
- The Film's lifespan depends on environmental exposure, maintenance, driving conditions, storage, and installation quality