

NANOPROOF

SOLAR FILMS

NANOPROOF TECHNICAL SPECIFICATIONS

ZR SERIES

Product Code	Thickness	Visible Light Transmittance (VLT)	UV Rejection	BTU Rejection (400mm to 950mm)	IRR Rejection (940nm to 1400nm)	IRR Rejection (760nm to 1750nm)	TSER	Shade Level
ZR - 02	2 MIL	2.2%	99.9%	92.5%	91.0%	91.0%	76.0%	90.0%
ZR - 05	2 MIL	5.0%	99.9%	91.5%	92.0%	91.0%	73.0%	70.0%
ZR - 10	2 MIL	9.0%	99.7%	92.0%	93.0%	93.0%	70.0%	50.0%
ZR - 20	2 MIL	18.0%	99.8%	93.0%	93.5%	92.0%	66.0%	30.0%
ZR - 40	2 MIL	38.0%	99.5%	92.5%	91.5%	90.0%	60.0%	10.0%
ZR - 70	2 MIL	71.0%	98.0%	93.5%	90.0%	90.0%	52.0%	0/0

WARRANTY

Durability

7 Years

- ZR series comes with a 7 year warranty against delamination, peeling, blistering, failure of adhesion, and other manufacturing defects.
- The Film's lifespan depends on environmental exposure, maintenance, driving conditions, storage, and installation quality